



Full-HD 2MP, Outdoor PT Cannon Camera

CAM3022FIR-PoE



- ▶ Support easy installation with NAT transversal DDNS server for port setting free
- ▶ Built - in Motion Detection & Email Notification
- ▶ Resolution up to 1920x1080@30FPS
- ▶ 19IR-leds with mechanical ICR and auto light sensor for day & night monitoring
- ▶ Support connectivity with iPhone, smart-phones and all browsers including Firefox, Chrome, Safari and Opera

Specification

System

RAM	4GB DDR
Flash ROM	16MB

IR Led

Auto/Manual mode, 20~25 meters visible

Spectral band width 42nm, Peak emission wavelength 850nm.

Daylight sensor, angle +/-65, wave length 400~700nm.

Protocol

Network Protocol TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP and RTSP

Physical

10 baseT or 100 baseT Fast Ethernet auto negotiation

Algorithm supported

H.264/MPEG4/MJPEG multi-codec for streaming video
JPEG for still image

Pan/Tilt angle

Support multi - direction movement

Pan: 150° (-75° ~75°)

Tilt: 95° (-75° ~20°)

Operating Environment

Temperature	-20 ~ 50°C
Humidity	85% RH

Dimension

Height	210mm
Diameter	115mm

Camera specification

Type 1/2.7" color CMOS sensor
Resolution 1920x1080
1.0Lux/F2.0 , AGC, AWB, AEC

Lens

Lens Fixed-focal length 4mm, F2.0,
Fov: 62°

Video Resolution

Video Resolution 1920x1080, 1280x1024, 1280x800,
640x480, 320x240, 176x144
Frame Rate Up to 30 FPS

Audio

AMR/G.726

Power

Input 100-240VAC, 50/60Hz, 0.7A
Output 12VDC, 1.5A
Consumption Max 12 W,
Support 802.3af compliant Power over Ethernet

I/O Interface

RJ-45, DI / DO,
Mic-In, Audio out
DC Power
Micro SD(inside camera)

EMI & Safety

CE, FCC

Weight

NET 800g (With bracket : 1000g)