



# IR-30M \_H.265\_4MP\_Network Bullet Camera

## CAM6092QIR-PoE CAM6092QIR-W



### Specification

#### Hardware

|                   |  |
|-------------------|--|
| CPU               | Multimedia SoC   |
| RAM               | 512MB  |
| Flash ROM         | 32MB   |
| Image Sensor      | 1/3" Mega-Pixel CMOS   |
| Lens              | Vari-focal Lens 2.8-12 mm @ F1.4   |
| IR Distance       | 30 Meters  |
| IR LED            | 28 Unites 5φ + 2 Units High Power IR LEDs                                    |
| Min. Illumination | Color: 0.08 lux (AGC ON)<br>B/W: 0.03 lux (AGC ON)                           |
| Day / Night       | Built-in Mechanism IR Cut Filter (ICR)                                       |
| Audio Input       | 1 Microphone in (3.5mm phone jack)   |
| Audio Output      | Support 2-way (3.5mm phone jack)   |
| Digital In / Out  | 1 Digital in / 1 Digital out (Terminal block)                                |
| Housing           | IP66 water proof standard  |
| Power Supply      | DC 12V Max: 6W(IR ON); 3.12W(IR OFF)<br>PoE Max: 7.68W(IR ON); 3.84W(IR OFF) |
| Dimensions        | Φ77.4 x L125 mm (w/o stand)  |
| Operating Temp    | -20°C ~ +60°C  |
| Weight.           | 720g   |

#### System

|                  |   |
|------------------|---|
| Video Resolution | 2592x1520@25fps,1920x1080@30fps, 1280x720@30fps,640x360@30fps   |
| Video Format     | H.265/H.264 / MJPEG   |
| Frame Rate       | Up to 30 FPS  |
| Triple Streaming | 2 for PC live view, 1 for mobile live view  |
| Bitrate Adjust   | CBR / VBR, up to 10Mbps   |
| Video Adjustment | Brightness, Contrast, Hue, Saturation, Sharpness, Gain control, ,WDR,Noise Reduction, Day/Night Adujustable,Flip,Mirror       |
| Audio Format     | G.711 (64Kbps)G.726 (24Kbps / 32Kbps)   |
| Privacy Mask     | 3 definable areas   |
| Security         | Password protection, IP address filtering, HTTPS encrypted data transmission, IEEE 802.1x port-based authentication, QoS/DSCP |
| Firmware Upgrade | HTTP mode, can be upgraded remotely   |

#### Event System

|                 |  |
|-----------------|--|
| Event Trigger   | Motion Detection, IP check, ,Network break down (wire only),Schedule     |
| Trigger Actions | Send Email, Send to FTP, Save to SD Card, Save to Samba HDD, Digital Out |
| Motion Area     | 3 definable areas  |

- ▶ 4Mega-Pixel CMOS Sensor
- ▶ Resolution up to 2592X1520@25FPS
- ▶ H.265/H.264/MJPEG formats & triple stream
- ▶ Embedded ICR and 30-meters IR LED for day & night 24-hours surveillance
- ▶ Two-way audio, Digital In/Out
- ▶ IP66 water proof standard
- ▶ Free 36CH recording software
- ▶ Free App (wecam\_p2p) for monitoring via Android/iOS smart phone



### Network

|                  |  |
|------------------|--|
| Ethernet         | 10 / 100 Base-T  |
| Wireless         | 802.11b/g/n, supports WPA-PSK, WPA2-PSK, WEP 64/ 128 bit   |
| CAM6092QIR-W     |  |
| Network Protocol | IPv4/IPv6, HTTP, HTTPS, TCP/IP, RTP/RTSP, UDP, 3GPP, SMTP, FTP, Samba, PPPoE, DHCP, DDNS, NTP, UPnP, SNMP, QoS/DSCP, IP Filter, IEEE 802.1x, Bonjour |

### Micro SD Card Management

|                   |   |
|-------------------|---|
| Recording Trigger | Motion Detection, Digital In, Tampering Detection, IP Check, Network Disconnect |
| Schedule          | Snapshot with schedule  |
| Video Format      | Video (AVI), Snapshot (JPEG)  |
| Playback / Delete | Yes   |

### Remote Client Access

|                   |  |
|-------------------|--|
| Client Software   | Microsoft IE 10 or above<br>Safari V5.1 or above   |
|                   | Android => "wecam_p2p"<br>iOS=> "wecam_p2p"  |
| Connected Clients | Up to 10 clients simultaneously  |
| PC Requirement    | OS: Windows 7,10<br>Suggested Hardware:<br>Intel Core 2 Duo 2.53GHz, RAM: 1GB<br>Graphic card: 128MB onboard |