



IR-70M _4MP_H265_Network Bullet Camera

CAM6098QIR-PoE

CAM6098QIR-W



- ▶ 4Mega-Pixel CMOS Sensor
- ▶ Resolution up to 2592x1520@30FPS
- ▶ H.265 /H.264/MJPEG formats & triple stream
- ▶ Day & Night Manual Switch Time Control
- ▶ Two-way audio, Digital In/Out
- ▶ IP66 water proof standard
- ▶ Free 36CH recording software
- ▶ IR LED Build-in 70M
- ▶ Auto Focus 10X Zoom Lens
- ▶ ROI Function
- ▶ Quadruple Streaming
- ▶ Free App (wecam_p2p) for monitoring via Android/iOS smart phone

Specification

Hardware

CPU	Multimedia SoC
RAM	512MB
Flash ROM	32MB
Image Sensor	1/3" Mega-Pixel CMOS
Lens	Auto Focus 10X Zoom Lens, Vari-focal length 2.8~12mm , F1.6
IR Distance	70 Meters
IR LED	8 Units High Power IR LEDs,850nm
Min. Illumination	Color: 0.08 lux (IR Off) Mono: 0.03 lux (IR ON)
Day / Night	Built-in Mechanism IR Cut Filter (ICR)
Audio Input	1 Microphone in (3.5mm phone jack)
Audio Output	1 Line out (3.5mm phone jack)
Digital In / Out	1 Digital in / 1 Digital out (Terminal block)
Video Output	1 Analog video out (BNC connector)
Housing	IP66 water proof standard
Power Supply	CAM6098QIR-W: Use Power Adaptor: DC 12V, 7.92W(IR ON); 3.00W(IR OFF) CAM6098QIR -PoE (built-in PoE Splitter): Use PoE: PoE Injector (IEEE 802.3af) Or, use Power Adaptor: 9.6W(IR ON); 3.84W(IR OFF)
Dimensions	Φ77.4 x L172 mm (w/o stand)
Operating Temp	-20°C ~ +60°C
weight	1100g

System

Video Resolution	2592x1520@25fps, 1920x1080@30fps, 1280x900@30fps, 640x360@30fps
Video Format	H.265 / H.264 / MJPEG
Frame Rate	Up to 30 FPS
Quadruple Streaming	Yes
Bitrates Adjust	CBR / VBR
Video Direction	Normal: Landscape 16:9
ROI Function (Region Of Interest)	Yes
Video Adjustment	Brightness, Contrast, Hue, Saturation, Sharpness, Gain control, Digital WDR, Digital Noise Reduction, Day/Night color mode, AGC, Flip, Mirror
Audio Format	G.711 (64Kbps)G.726 (24Kbps / 32Kbps)
Privacy Mask	3 definable areas
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, IEEE 802.1x port-based authentication, QoS/DSCP
Firmware Upgrade	HTTP mode, can be upgraded remotely



Network

Ethernet	10 / 100 Base-T
Wireless(Optional)	802.11b/g/n, supports WPA-PSK, CAM6082QIR-W WPA2-PSK, WEP 64/ 128 bit
Network Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, RTP/RTSP, UDP, 3GPP, SMTP, FTP, Samba, PPPoE, DHCP, DDNS, NTP, UPnP, SNMP, QoS/DSCP, IP Filter, IEEE 802.1x, Bonjour

Remote Client Access

Client Software	Microsoft IE 9 or above Safari V5.1 or above
	Android => "wecam_p2p" iOS=> " wecam_p2p "
Connected Clients	Up to 10 clients simultaneously
PC Requirement	OS: Windows 7, Vista, XP Suggested Hardware: Intel Core 2 Duo 2.53GHz, RAM: 1GB Graphic card: 128MB onboard

Micro SD Card Management (Optional)

Recording Trigger	Motion Detection, IP Check, Network Disconnect, Schedule, DI
Schedule	Snapshot with schedule
Video Format	Video (AVI), Snapshot (JPEG)
Playback / Delete	Yes

Event System

Event Trigger	Motion Detection, Digital In, Tampering Detection, Sound Detection(MIC-in)
Trigger Actions	Send Email, Send to FTP, Save to SD Card, Save to Samba HDD, Digital Out
Motion Area	3 definable areas
Pre / Post Alarm	Yes, configurable time