



H.264 2Mega-Pixel IR-50M IP Camera

CAM625MIR(PoE)



- ▶ 2 Mega-Pixel CMOS Sensor
- ▶ H.264/MJPEG/MPEG4 Triple mode & streaming
- ▶ IR distance up to 50 meters
- ▶ Onvif Compliant
- ▶ IP-66 waterproof standard
- ▶ 2-way audio
- ▶ Digital I/O: 1 in/ 1 Relay out
- ▶ Free App (iCAM-Smart) for monitoring via smart phone
- ▶ Embedded PoE (CAM625MIR-PoE)
- ▶ Free 36CH recording software

Specification

Hardware

| | |
|---------------|--|
| CPU | ARM 9, 32 bit RISC |
| RAM | 256MB |
| Flash | 16MB |
| Image Sensor | 1/3" CMOS, 2 Mega pixel |
| Lens | Vari-focal Auto Iris 3.6 ~ 16 mm |
| Illumination | IR On: 0 lux |
| IR Distance | 50 Meters |
| Audio In/ Out | 1 Mic in / 1 Line out |
| Digital I/O | 1 In / 1 Relay out |
| Video out | 1 analog out (BNC connector) |
| Water Proof | IP-66 standard |
| Power Supply | CAM625MIR: DC 12V, 1.5A CAM625MIR-PoE: Use PoE: PoE Injector (IEEE 802.3at) Or, use Power Adaptor: DC 12V, 1.5A |
| Dimensions | W142 x H302 x L432 mm |
| Temperature | -10°C ~ +40°C |

Network

| | |
|------------------|---|
| Ethernet | 10/ 100 Base-T |
| Network Protocol | HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP |

Client Requirements

| | |
|-----------|---|
| OS | Windows XP / Vista / Win 7 |
| Browser | IE7,IE8, FireFox, Safari, Chrome, Opera |
| Suggested | Intel Dual Core: 1.66GHz, RAM: 1GB, Graphic card: 128MB onboard RAM |

Event System

| | |
|-----------------|--------------------------------------|
| Event Trigger | Motion Detection, Sensor In |
| Trigger Actions | Send Email, Send to FTP, Digital Out |

System

| | |
|----------------------|--|
| Video Resolution | 1600x1200, 1280x1024,1280x960, 1280x720, 800x592, 640x480 320x240, 176x144 |
| Compression Format | H.264/ MJPEG/MPEG-4(3GPP only) |
| Frame Rate | Up to 15FPS@1600x1200 Up to 30 FPS@1280x720 |
| Video Bitrate Adjust | CBR, VBR |
| Triple Streaming | Yes |
| 3GPP | Yes, Live view with 3G mobile phone |
| Image Snapshot | Yes |
| Video Adjust | Brightness, Contrast, BLC, Sharpness, Night Mode |
| Motion Detection | Yes, 3 different areas |
| Pre/ Post Alarm | Yes, configurable |
| Security | Password protection |
| Connection | Up to 10 clients simultaneously |
| Firmware Upgrade | HTTP mode, remotely |
| Audio | Yes, 2-way |

SD Card Management

| | |
|-------------------------|---|
| Recording Trigger | Motion Detection, Sensor In, IP Check, Network Disconnect |
| Video Format | Video (AVI), Snapshot (JPEG) |
| Schedule | Snapshot during schedule |
| Video Playback / Delete | Yes |

Package List



PoE Model doesn't include power adaptor