




2 Mega-Pixel IR-80M CMOS IP Camera

CAM627M (W,PoE)



- ▶ H.264 /MJPEG /MPEG4 Triple mode & streaming
- ▶ IR distance up to 80 meters
- Onvif Compliant
- ▶ 2-way audio / 1 Analog video output
- ▶ Digital I/O: 1 Relay out
- Free App (iCAM-Smart) for monitoring via smart phone
- ► Embedded PoE (CAM627M-PoE)
- ▶ Free 36CH recording software

Specification

Hardware

CPU/ RAM/ Flash ARM 9, 32 bit RISC/ 256MB/ 16MB

Image Sensor 1/3" CMOS, 2 Mega-Pixels

Lens Vari-focal 10 ~ 40 mm, F1.4 ~ 360

IR Distance 80 Meters
Illumination IR On: 0 lux
Infrared LED 850nm / 8 LED
Lens Changeable Yes, CS Mount

Support DC IRIS Yes

Video Out 1 Analog video out (BNC connector)

Water Proof IP-66 standard Audio In Built-in microphone

Audio Out 1 Line out
Digital I/O 1 Relay out

Power Supply CAM627M: DC 12V, 2A

CAM627M-PoE:

Use PoE Injector (IEEE 802.3at)High power PoE Injector is included

Dimensions W170 x H280 x L470 mm

Temperature -10° C $\sim +40^{\circ}$ C

Network

Ethernet 10/ 100 Base-T

Wireless 802.11 b/g/n (CAM627M-W)

WEP, WPA-PSK, WPA2-PSK

Network Protocol HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP,

FTP, PPPoE, DHCP, DDNS, UPnP

Client Requirements

OS Windows XP / Vista / Win 7

Browser IE7,IE8, FireFox, Safari, Chrome, Opera Suggested Intel Core 2 Duo 1.66GHz, RAM: 1GB

Graphic card: 128MB onboard RAM

System

Video Resolution 1600x1200,1280x1024,1280x960,

1280x720, 800x592,640x480,

320x240, 176x144

Compression Format H.264 / MJPEG / MPEG-4 (3GPP only)

Frame Rate Up to 15 FPS@1600x1200

Up to 30 FPS@1280x720

Video Bitrate Adjust CBR, VBR

Triple Streaming Yes (2 for live view, 1 for 3GPP)

Video Adjust Night Mode, Brightness, Contrast, BLC,

Sharpness

3GPP Yes, Live view with 3G mobile phone

Motion Detection Yes, 3 different areas
Pre/ Post Alarm Yes, configurable
Security Password protection

Connection Up to 10 clients simultaneously

Firmware Upgrade HTTP mode, remotely

Audio Yes, 2-way

Event System

Event Trigger Motion Detection

Trigger Actions Send Email, Send to FTP, Save to SD

Card, Relay Out

SD Card Management

Recording Trigger Motion Detection, Sensor In, IP Check,

Network Disconnect

Video Format Video (AVI), Snapshot (JPEG)
Schedule Snapshot during schedule

Video Playback / Delete Yes

Package List







PoE Model doesn't include power adaptor

http://www.a-soni.com

E-mail: marketing@a-soni.com

* Specifications are subject to change without notice