



2 Mega-Pixel H.264 CMOS Panoramic Network

CAM636MV



- 2 Mega-Pixel CMOS Sensor
- ► H.264 / MJPEG / MPEG4 (3GPP Only) compression formats.
- ▶ Supports resolution up to 1600x1200
- ► H.264 / MJPEG / MPEG4 (3GPP Only) triple streaming.
- ▶ Self-Contained HTTP Web Server providing Internet capability for remote access
- ▶ Built-in PoE splitter, support for Power over Ethernet (PoE model)

Specification

Hardware

CPU ARM 9, 32 bit RISC RAM / Flash 256MB / 16MB

Image Sensor 1/3" CMOS, 2 Mega pixels
Lens 1/2", 2.3mm, F2.0, Fisheye Lens

Day / Night Mechanism IR Cut Filter (ICR)

Illumination 0.5 lux

Audio In / Out 1 Line in / 1 Line out

Video Out 1 Analog video out (BNC connector)

Digital I/O 1 Digital in / 1 Relay out
Power Supply Normal model: DC 12V, 1A

PoE model (built-in PoE Splitter):
Use PoE: PoE Injector (IEEE 802.3af)
Or, use Power Adaptor: DC 12V, 1A

Oi, use i owel Adaptor.

Dimensions Φ 131.2 x H94.3 mm Temperature $-10^{\circ}\text{C} \sim +45^{\circ}\text{C}$

Network

Ethernet 10/100 Base-T

Network Protocol HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP,

SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

Event System

Event Trigger Motion Detection, Sensor In

Trigger Actions Send Email, Send to FTP, Save to SD Card,

Relay out

Client Requirements

OS Windows XP / Vista / Win 7

Browser IE7,IE8, FireFox, Safari, Chrome, Opera Suggested Intel Core2 Duo : 1.66GHz, RAM: 1024MB,

Graphic card: 128MB onboard RAM

System

Video Resolution 1600x1200, 1280x1024, 1280x960,

1280x720, 800x592, 640x480,

320x240,160x120

Compression Format H.264 / MJPEG / MPEG-4 (3GPP only)

Frame Rate Up to 15 FPS@1600x1200

Up to 30 FPS@1280x720

Video Bitrate Adjust CBR, VBR

Triple Streaming Yes (2 for live view, 1 for 3GPP)

3GPP Yes, Live view with 3G mobile phone

Image Snapshot Yes

Video Adjust Brightness, Contrast, Sharpness, BLC,

Night Mode

Motion Detection Yes, 3 different areas
Pre/ Post Alarm Yes, configurable
Security Password protection

Connection Up to 10 clients simultaneously

Firmware Upgrade HTTP mode, remotely

Audio Yes, 2-way

SD Card Management

Recording Trigger Motion Detection, Sensor In
Video Format Video (AVI), Snapshot (JPEG)
Other Functions IP Check, Network Disconnect,

Schedule Snapshot

Video Playback / Delete Yes

Package List







PoE Model doesn't include power adaptor

http://www.a-soni.com

E-mail: marketing@a-soni.com

* Specifications are subject to change without notice