



## 2 Mega-Pixel IR-12M 3-Axis Dome Camera

# CAM646MIR(PoE)



- ▶ H.264/MPEG4/MJPEG Triple mode & streaming
- Support Micro-SD card for event recording
- ▶ IR distance up to 12 meters
- Onvif Compliant
- ► Free App (iCAM-Smart) for monitoring via smart phone
- ▶ 1 Digital in / 1 Relay out
- ▶ 2-way audio
- ► Embedded PoE (CAM646MIR-PoE)
- ▶ Free 36CH recording software



## **Specification**

#### **Hardware**

CPU / RAM / Flash ARM 9, 32 bit RISC / 256MB / 16MB

Image Sensor 1/3" CMOS, 2.0 Mega pixels Lens Vari-focal 2.7 ~ 9 mm

IR Distance 12 Meters

Day/ Night Built-in Mechanism IR Cut Filter (ICR)

Illumination IR On: 0 lux

Video Out 1 Analog video out (BNC connector)

Audio In/ Out 1 Mic in / 1 Line out
Digital I/O 1 In / 1 Relay out

Power Supply CAM646MIR: DC 12V, 1A

CAM646MIR-PoE:

Use PoE: PoE Injector (IEEE 802.3af)
Or, use Power Adaptor: DC 12V, 1A

Dimensions  $\Phi$ 132 x H108.4 mm Temperature  $-10^{\circ}\text{C} \sim +45^{\circ}\text{C}$ 

#### **Network**

Ethernet 10/ 100 Base-T

Network Protocol HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP,

SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

### **Event System**

Event Trigger Motion Detection, Sensor In

Trigger Actions Send Email, Send to FTP, Save to SD Card,

Relay Out

## **Client Requirements**

OS Windows XP / Vista / Win 7

Browser IE7,IE8, FireFox, Safari, Chrome, Opera Suggested Intel Core 2 Duo : 1.66G, RAM: 1GB,

Graphic card: 128MB onboard RAM

# **System**

Video Resolution 1600x1200, 1280x1024, 1280x960,

1280x720, 800x592, 640x480,

320x240,160x120

Compression Format H.264 / MJPEG / MPEG-4 (3GPP only)

Frame Rate Up to 15 FPS@1600x1200

Up to 30 FPS@1280x720

Video Bitrate Adjust CBR, VBR

Triple Streaming Yes ( 2 for live view, 1 for 3GPP)

3GPP Yes, Live view with 3G mobile phone

Image Snapshot Yes

Video Adjust Brightness, Contrast, Sharpness, BLC,

Night Mode

Privacy Mask Yes, 3 different areas
Motion Detection Yes, 3 different areas
Pre/ Post Alarm Yes, configurable
Security Password protection

Connection Up to 10 clients simultaneously
Audio Yes, 2-way(Duplex Support)

Firmware Upgrade HTTP mode, remotely

#### **SD Card Management**

Recording Trigger Motion Detection, Sensor In, IP Check,

Network Disconnect

Video Format Video (AVI), Snapshot (JPEG)
Schedule Snapshot during schedule

Video Playback / Delete Yes

## **Package List**







PoE Model doesn't include power adaptor

http://www.a-soni.com

E-mail: marketing@a-soni.com

\* Specifications are subject to change without notice