

2 Mega-Pixel CMOS Day&Night Dome

CAM649MB(PoE)



- ► H.264/MPEG4/MJPEG Triple mode & streaming
- Onvif Compliant
- Support SD card for event recording
- ► Free App (iCAM-Smart) for monitoring via smart phone
- ▶ 1 Analog video output
- ▶ IP66 waterproof standard
- 2-way audio
- ► Embedded PoE (CAM649MB-PoE)
- ▶ Free 36CH recording software

Specification

soni

Hardware

CPU ARM 9, 32 bit RISC

RAM 256MB Flash 16MB

Image Sensor 1/3" CMOS, 2.0 Mega pixels

Lens Vari-focal 2.7 ~ 9 mm

Day / Night Embedded IR Cut Filter (ICR)

Illumination 0.5 lux

Video Out 1 Analog video out (BNC connector)

Audio In/ Out 1 Mic in / 1 Line out
Digital I/O 1 In / 1 Relay out

Power Supply CAM649MB: DC 12V, 1A

CAM649MB-PoE:

Use PoE: PoE Injector (IEEE 802.3af)
Or, use Power Adaptor: DC 12V, 1A
Φ127mm x W200.7mm x H204.4mm

Dimensions Φ127mm x W200.7mm x H204.4mn

Temperature -10° C ~ $+45^{\circ}$ C

Network

Ethernet 10/ 100 Base-T

Network Protocol HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP,

SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

Event System

Event Trigger Motion Detection, Sensor In

Trigger Actions Send Email, Send to FTP, Save to SD Card,

Relay Out

Client Requirements

OS Windows XP / Vista / Win 7

Browser IE7,IE8, FireFox, Safari, Chrome, Opera
Suggested Intel Core 2 Duo : 1.66GHz, RAM: 1024MB,

Graphic card: 128MB onboard RAM

System

Video Resolution 1600x1200, 1280x1024, 1280x960,

*Optional Indoor Model - CAM649MC / CAM649MD

1280x720, 800x592, 640x480,

320x240,160x120

Compression Format H.264 / MJPEG / MPEG-4 (3GPP only)

Frame Rate Up to 15 FPS@1600x1200

Up to 30 FPS@1280x720

Video Bitrate Adjust CBR, VBR

Triple Streaming Yes (2 for live view, 1 for 3GPP)

3GPP Yes, Live view with 3G mobile phone

Image Snapshot Yes

Video Adjust Brightness, Contrast, Sharpness, BLC,

Night Mode

Motion Detection Yes, 3 different areas
Pre/ Post Alarm Yes, configurable
Security Password protection

Connection Up to 10 clients simultaneously
Audio Yes, 2-way(Duplex Support)

Firmware Upgrade HTTP mode, remotely

SD Card Management

Recording Trigger Motion Detection, Sensor In, IP Check,

Network Disconnect

Video Format Video (AVI), Snapshot (JPEG)
Schedule Snapshot during schedule

Video Playback / Delete Yes

Package List









PoE Model doesn't include power adaptor