


/Isoni

1080P 2 Mega-Pixel CMOS IR-12M Vandal Dome

CAM669FIR(PoE)



- ▶ H.264/MPEG4/MJPEG Triple mode & streaming
- Support D-WDR / DNR /8 steps manual shutter
- ▶ 30FPS@1920x1080
- Onvif Compliant
- Support Micro SD card for event recording
- IR distance up to 12 meters
- Free App (iCAM-Smart) for monitoring via smart phone
- ▶ 2-way audio
- Embedded PoE (CAM669FIR-PoE)
- Free 36CH recording software

Specification

Hard	ware
------	------

CPU ARM 9, 32 bit RISC

RAM 256MB Flash 16MB

Image Sensor 1/2.7" CMOS, 2.0 Mega pixels Lens Vari-focal $3.3 \sim 12$ mm, F1.4

IR Distance Up to 12 Meters

Day/ Night Embedded IR Cut Filter (ICR)

Illumination IR On: 0 Lux Audio In/ Out 1 Mic in

1 Line out (Internal terminal block)

Digital I/O 1 In / 1 Relay out
Power Supply CAM669FIR: DC 12V, 1A

CAM669FIR-PoE:

Use PoE: PoE Injector (IEEE 802.3af)
Or, use Power Adaptor: DC 12V, 1A

Dimensions $\Phi 134 \times H108 \text{ mm}$ Temperature $-10^{\circ}\text{C} \sim +45^{\circ}\text{C}$

Network

Ethernet 10/ 100 Base-T

Network Protocol HTTP, HTTPS,TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

Event System

Event Trigger Motion Detection, Sensor In Trigger Actions Send Email, Send to FTP,

Save to Micro SD Card, Relay Out

Client Requirements

OS Windows XP / Vista / Win 7

Browser IE7,IE8, FireFox, Safari, Chrome, Opera Suggested Intel Dual Core : 2.53G, RAM: 1GB,

Graphic card: 128MB onboard RAM

System

Video Resolution 1920x1080, 1280x720, 640x480,

320x240, 176x144

Compression Format H.264 / MJPEG / MPEG-4 (3GPP only)

Frame Rate Up to 30 FPS@1920x1080

Video Bitrate Adjust CBR, VBR

Triple Streaming Yes (2 for live view, 1 for 3GPP)

3GPP

Yes, Live view with 3G mobile phone

Image Snapshot Yes

Video Adjust Brightness, Contrast, Hue, Saturation,

Sharpness, AGC, Manuals shutter adjust, D-WDR, Night Mode, Flip, Mirror, Noise reduction, Exposure, Day

& Night adjust

Motion Detection Yes, 3 different areas
Pre/ Post Alarm Yes, configurable
Security Password protection

Connection Up to 10 clients simultaneously

Audio Yes, 2-way

Firmware Upgrade HTTP mode, remotely

Micro SD Card Management

Recording Trigger Motion Detection, Sensor In, IP

Check, Network Disconnect

Video Format Video (AVI), Snapshot (JPEG)
Schedule Snapshot during schedule

Video Playback / Delete Yes

Package List









PoE Model doesn't include power adaptor