



22X H.264 Mega-Pixel PTZ Dome IP Camera

CAM672S-AP (W,PoE)



- ▶ H.264/ MPEG4/ MJPEG Triple mode & streaming
- ▶ Optical Zoom: 22X ; Support Sense Up
- ▶ Support Digital Image Stabilizer ; DNR
- ▶ Support manual shutter ; D-WDR
- ▶ Support Micro SD card for event recording
- ▶ Digital I/O: 2 in/ 1 out ; 2-way audio
- ▶ Embedded PoE (CAM672SA-PoE)
- ▶ Optional Wireless (CAM672SA-W)
- ▶ Free 36CH recording software

Specification

Hardware

CPU/ RAM/ Flash	ARM 9, 32 bit RISC/ 256MB/ 16MB
Image Sensor	1/3" Panasonic CMOS , 1.3 Mega-Pixel
Lens	Auto focus zoom lens, 4.7 ~ 103.4 mm, F1.6 ~ F3.1
Illumination	0.1 Lux
Day/ Night	Auto, IR Cut Filter
Audio In	3.5 mm headphone jack
Audio Out	3.5 mm headphone jack
Digital I/O	2 In / 1 Out
Power Supply	CAM672SA / CAM672SA-W: DC 12V, 3A CAM672SA-PoE: Use PoE: PoE Injector (IEEE 802.3at) Or, use Power Adapter: DC 12V, 3A
Dimensions	W221 x H336 x D320 mm
Temperature	-5°C~ +45°C

Network

Ethernet	10/ 100 Base-T
Wireless	802.11 b/g/n (CAM672SA-W) WPA-PSK, WPA2-PSK, WEP 64 / 128 bit
Network Protocol	HTTP, HTTPS,TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, Access list, DDNS,QoS/DSCP, UPnP, IEEE 802.1X,UDP

Client Requirements

OS	Windows XP / Vista / Win 7
Browser	IE7,IE8, FireFox, Safari, Chrome, Opera
Suggested	Intel Core 2 Duo 2.53, RAM: 1024MB, Graphic card: 128MB onboard RAM

Event System

Event Trigger	Motion Detection, Sensor In
Trigger Actions	Send Email, Send to FTP, Save to Micro SD Card, Digital Out

System

Video Resolution	1280x1024, 1280x960, 1280x720, 640x480, 320x240, 176x144
Compression Format	H.264 / MJPEG / MPEG-4
Frame Rate	1280x1024 @ 30 FPS
Video Bitrate Adjust	CBR, VBR
Triple Streaming	Yes
3GPP	Yes, Live view with smart phone
Pan/ Tilt/ Zoom Control	Yes, remotely
Zoom Ratio	Optical: 22X, Digital: 4X
Pan/ Tilt Angle	Pan: 0 ° ~320°, Tilt: 0 ° ~90°
Preset Point	128 Preset points
Patrol	8 groups, user defined
Auto Pan	Yes
Pan/ Tilt Speed Control	Yes, 200°/S
Motion Detection	Yes, 3 different areas
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way

Micro SD Card Management

Recording Trigger	Motion Detection, Sensor In, IP Check, Network Disconnect
Video Format	Video (AVI), Snapshot (JPEG)
Schedule	Snapshot during schedule
Video Playback	Yes

Package List



Antenna: CAM672SA-W

PoE Model doesn't include power adaptor