



## H.264 VGA CMOS IP Camera

# CAM677G(PoE)



- ▶ VGA CMOS sensor
- ▶ H.264/ MPEG4/ MJPEG Triple Mode & Streaming
- ▶ 30FPS@ 640x480
- ▶ Onvif Compliant
- ▶ Digital I/O: 1 In / 1 Out
- ▶ 2-way audio
- ▶ Free App (wecam\_p2p) for monitoring via smart phone
- ▶ Optional Wireless (CAM677G-W)
- ▶ Free 36CH recording software

### Specification

#### Hardware

CPU	ARM 9, 32 bit RISC
RAM	128MB
Flash	16MB
Image Sensor	1/4" CMOS
Lens	Fixed lens 6mm @ F1.6
Lens Changeable	Yes, CS mount
Illumination	1 lux
Audio In	Built-in microphone
Audio Out	3.5mm headphone jack
Digital I/O	1 In / 1 Out
Power Supply	DC 12V, 1A
Dimensions	W56 x H50 x D126 mm
Temperature	-10°C ~ +45°C

#### Network

Ethernet	10/ 100 Base-T
Wireless	802.11 b/g/n (CAM677G-W) WPA-PSK, WPA2-PSK, WEP 64 / 128 bit
Network Protocol	HTTP, HTTPS, TCP/IP, RTP/RTSP, UDP, 3GPP, NTP, SMTP, FTP, PPPoE, Samba, DHCP, DDNS, UPnP, SNMP, QoS/DSCP, IP Filter, IEEE802.1x, IPv4/IPv6

#### Client Requirements

OS	Windows XP / Vista / Win 7
Browser	IE7, IE8, FireFox, Safari, Chrome, Opera
Suggested	Intel Core 2 Duo 2.53GHz, RAM: 1GB Graphic card: 128MB onboard RAM

#### System

Video Resolution	640x480, 320x240, 176x144
Compression Format	H.264 / MJPEG / MPEG-4
Frame Rate	Up to 30 FPS@640x480
Video Bitrate Adjust	CBR, VBR
Triple Streaming	Yes
3GPP	Yes, Live view with smart phone
Image Snapshot	Yes
Video Adjust	Brightness, Contrast, Saturation, Exposure, Sharpness, AGC, BLC, Night Mode, Flip, Mirror, Outdoor / Indoor
Motion Detection	Yes, 3 different areas
Privacy Mask	Yes, 3 different areas
Pre/ Post Alarm	Yes, configurable
Security	Password protection
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely

#### Event System

Event Trigger	Motion Detection
Trigger Actions	Send Email, Send to FTP

#### Package List



CD & Manual



Screw



Antenna:  
CAM677G-W