

Asoni

ONVIF



9CH Digital Video Recorder

DVR6109H



- ▶ Support up to 8-channel 1080P aHD/TVI cameras input.
- ▶ Support up to 8-channel Analog cameras input.
- ▶ Support up to 3-channel IP cameras input.
- ▶ Support H.264 decoding & encoding.
- ▶ Analog camera recording rate up to 120 FPS @ 1080P.
- ▶ Real-time Display & Playback.
- ▶ Support 2 Megapixel IP Camera for IP camera channel.
- ▶ Audio: 4 in & 1 out.
- ▶ Support 6T HDDs x1.
- ▶ Support CMS (Central Management System) control.
- ▶ Support time-point backup function under Ethernet remote control mode. User can select any time period to process backup from remote side.
- ▶ Support time-search & event-search function under Ethernet remote control mode. Up to four online clients for independent remote control; individual live-time, play-back & time-search function available
- ▶ Support PPPoE/ Static/ DHCP IP & DDNS.

Video / Audio

IP Cam Video Input	Max 3 channels
IP Cam Resolution	Up to 2 Megapixel
IP Cam Frame rate	Up to 20 FPS @ per CH
Analog Video Input	Max 8 channels
Analog Resolution	1080P NTSC: 1920 x 1080 PAL: 1920 x 1080 720P NTSC: 1280 x 720 PAL: 1280 x 720 960H NTSC: 960 x 480 PAL: 960 x 576 D1 NTSC: 720 x 480 PAL: 720 x 576
Analog Live-time Display Rate	8 x 30 Frame /sec (NTSC)
IP Cam Audio Input	8 x 25 Frame /sec (PAL)
Analog Audio Input	Max 3 channels Max 4 channels

Specification

Hardware

Vedio Input	BNV x 8
Vedio Output	VGA x1 / HDMI x1 / BNC x1
Audio input	RCA x4 for CH1 ~CH4
Audio output	RCA x1 for speaker
Ethernet	RJ-45, 10/100/1000 Mbps
USB	x1

Hybrid DVR Functions

OS	Embedded Linux
Camera Name	Max. 20 characters
Screen Split Control	1, 4, 9
Image Control	Contrast / Brightness / Saturation / Hue
Recording mode	Manual / Schedule / Alarm

System Monitoring and Recovery

Monitoring	Watchdog
------------	----------

Searching and Playback

Search Method	Date / Time / Event
Date/ Time / Event Search	Selectable on the calendar
Log Search	Through the log data to find the video event / time
Playback Speed	Fast Forward X 2 X8 X 16 X32 X64 Picture by picture Playback Pause Fast Backward X2 X4 X8
Recording Resolution	1080P 720P 960H D1 Half D1 CIF
Recording Rate Per Channel	1080P Simplex: Up to 15fps Duplex: Up to 12fps 720P NTSC: Up to 30 FPS PAL: Up to 25 FPS
Backup Type	USB

STORAGE & BACKUP DEVICE

Internal HDD Support	SATA HDD x 1
External USB Backup Device	USB x2

Networking

Type	Static/ DHCP/ PPPoE/DDNS
------	-----------------------------

Language

Type	English / Traditional Chinese / Simple Chinese / Russian / Italian / Japanese / Czech / France / Germany / Spanish / Portuguese
------	---

Physical

Color	Black
Dimensions (W x H x D)	218mm x 44mm x 202mm
Weight	1000g

Remote Client Software

Monitoring Environment	Hunt CMS, IPMotion
IP / Analog cam Live View	9 Channels
Remote Search	Web site remote time / event search

Environment

Operating Temperature	-10~55°C / 14~131°F
Humidity	0~80% RH (non-condensing)