Network Surveillance Solutions



4CH mini Network Video Recorder

NVR6204M

- Linux-based standalone NVR, H.264 decoding
- Manage up to 4 IP cameras, Supports 5 Mega-pixel
- Plug & Play, Real-time Display & Audio Backup & Playback for all channels
- Manual / schedule / event recording
- Various types of event alerts
- Support time-point backup function under Ethernet remote control mode
- USB3.0 connector connects to external storage
- Support HDD up to 8TB Max
- Remote client access and management
- Free App (wecam_p2p, iCAM Smart) for monitoring via Android / iOS smart phone

Specification

System

CPU / OS	Multimedia SoC / Embedded Linux	Live View
Network	Gigabit Ethernet port x1	Split Screen
Video Output	VGA x 1, HDMI x 1, up to 1920x1080	Event Notification
USB Connector	USB 2.0 x 1, USB 3.0 x 1 (for mouse or \checkmark	PTZ Control
	USB storage)	Digital Zoom
Audio Input	3.5mm jack to connect microphone	Privacy Mask
Audio Output	3.5mm jack to connect amplified speaker	Channel Identify
Record Storage	Internal Storage: SATA HDD x 1,(up to	
	8TB total)	Playback and Back
	External Storage:	Search Method
	USB Backup Disk	Search Method
Network Protocol Mouse Control	HTTP, TCP/IP, RTP/RTSP, SMTP, FTP, PPPoE, DHCP (Server & Client), DDNS, NTP, UPnP Yes	Log Search Backup
Authority Control	Password protection	Event System
System Monitor	Watchdog	Alarm Event Mo
Power Supply	DC 12V, 3A (without HDD)	Trigger Actions Re
Dimensions	W60 x H161 x D208 mm	Remote Client Acc
Operating Temp.	0~45°C / 32~113°F	Client Software
Humidity	0~80% RH (non-condensing)	

Split Screen	1, 4, Full screen		
Event Notification	On screen icon / buzzer notification		
PTZ Control	Yes ,(CAM6_series preferred)		
Digital Zoom	Yes		
Privacy Mask	Yes		
Channel Identify	Yes, Max.	20 characters for channel	
	name		
Playback and Back	ar		
Search Method	-	arch, Date / Time , Event	
		om calendar)	
		eo from Log table	
Backup		USB storage	
· /		J	
Event System			
Alarm Event Motion / Digita		l Input / Video Loss / Power	
Trigger Actions Rec	ording / E-I	Mail / FTP / Buzzer Warning	
Remote Client Access			
Client Software M	icrosoft IE	11 or above	
S	afari V5.1 d	or above	
A	ndroid =>	"wecam_p2p"	
	i0S=> "i	CAM Smart"	
Connected Clients U	p to 4 clien	ts simultaneously	
Remote Operation Li	Live view / Playback / Setup / Backup		
PC Requirement O	OS: Windows 7, Vista, XP		
S	Suggested Hardware:		
Ir	ntel Core 2 Duo 2.53GHz, RAM: 1GB		

Video / Audio

Channel	Max. 4 channels recording and display
Support IPCam	Up to 5 Mega-pixel 2592x1944
	H.264 compression mode
Frame Rate	Up to 30FPS per channel
Throughput	Up to 28Mbps
2-Way Audio	Hearing voice from IP camera
	Chatting or broadcasting to IP cameras

Recording

Record Format
Record Resolution
Record FPS
Record Mode
Pre Recording
HDD Management

H.264 video stream Depends on IP camera Up to 5 Mega-pixel 2592x1944 Depends on IP camera, up to 30FPS Manual / Schedule / Event 5~15 sec Overwrite when HDD is full Auto delete after selected days

Connection Diagram

