



36CH Linux Network Video Recorder

NVR6536L(P)



- ▶ Support up to 36 channel H.265/H.264 IP camera
- ▶ Manage up to 16 channel PoE for IP cameras input
- ▶ Supports up to 8 Mega-pixel
- ▶ Power management for PoE channel
- ▶ Plug & play for easy installation
- ▶ Support e-SATA external storage
- ▶ Support RAID1/5 (optional)
- ▶ VGA& HDMI dual output, HDMI up to 4K2K
- ▶ Playback Smart search
- ▶ E-MAP
- ▶ Manual / schedule / event recording
- ▶ Free App (wecam_p2p) for monitoring via Android / iOS smart phone
- ▶ Peer to Peer (NVR65 Series LP)

Specification

System

Video Output	VGA x 1 up to 1080P HDMI x 1, up to 4K2K
USB Connector	USB 2.0 x 3
Audio Input	3.5mm jack to connect microphone
Audio Output	3.5mm jack to connect amplified speaker
Record Storage	Internal Storage: SATA HDD x 8 External Storage: Local USB2.0x3, eSATA: x2 RAID: RAID 1/5 (Optional)
Power Supply	AC 100~240V
Power Output	RJ-45 x 16, PoE 802.3at
Max. Power supply	190W
Operating Temp.	0~45°C / 32~113°F
Humidity	0~80% RH (non-condensing)
GPIO	4 Alarm in/ 1 Relay out
WAN Ethernet	RJ-45 x1, 10/100/1000 Mbps
LAN Ethernet	RJ-45 x16, 10/100 Mbps

Recording

Record Mode	Manual / Schedule / Event
Pre Recording	5~60 sec
Playback search	Timeline search, Event list search, Smart search

Remote Client Access

Client Software	Microsoft IE 11 or above Chrome Safari V5.1 or above Android => "wecam_p2p" iOS=> "wecam_p2p"
Connected Clients	Up to 10 clients simultaneously

Video / Audio

Channel	Max.36 channels recording and display
IPCam Video input	36 channels
Split screen display	16CH(1, 4, 9, 16) 25CH(1, 4, 9, 16, 25) 36CH (1, 4, 9, 16, 25, 36)
Decompression	H.265, H.264
IP Cam Resolution	Up to 4K2K
Throughput	(150Mbps)