



IR-30M_5MP_H265_Network Bullet Camera

CAM6088EIR-PoE

CAM6088EIR-W



Specification

- ▶ 5Mega-Pixel CMOS Sensor
- ▶ Resolution up to 2592x1944@30FPS
- ▶ H.265 /H.264/MJPEG formats & triple stream bandwidth saving up to 50%
- ▶ External Vari-focal Lens Adjustment
- ▶ Embedded ICR and 30meters IR LED for day & night
- ▶ Two-way audio, Digital In/Out
- ▶ IP66 water proof standard
- ▶ Free 36CH recording software
- ▶ Free App (wecam_p2p) for monitoring via Android/iOS smart phone

Hardware

CPU	Multimedia SoC
RAM	512MB
Flash ROM	32MB
Image Sensor	1/3.2" Mega-Pixel CMOS
Lens	Vari-focal length 3~10.5mm, F1.4
IR Distance	30 Meters
IR LED	28 Units 5φ+ 2 Units High Power IR LEDs,850nm
Min. Illumination	Color: 0.5 lux (IR Off) Mono: 0.1 lux (IR ON)
Day / Night	Built-in Mechanism IR Cut Filter (ICR)
Audio Input	1 Microphone in (3.5mm phone jack)
Audio Output	1 Line out (3.5mm phone jack)
Digital In / Out	1 Digital in / 1 Digital out (Terminal block)
Video Output	1 Analog video out (BNC connector)
Housing	IP66 water proof standard
Power Supply	DC 12V Max: 5.88W(IR ON); 3.12W(IR OFF) PoE Max: 7.41W(IR ON); 3.99W(IR OFF)
Dimensions	Φ77.4 x L 125.5mm (w/o stand)
Operating Temp	-20°C ~ +60°C
weight	720g

System

Video Resolution	2592x1944@30fps, 2048x1536@30fps, 1920x1080@30fps, 1600x1200@30fps, 1280x960@30fps, 1280x720@30fps, 640x480@30fps, 320x240@30fps, 176x144@30fps
Video Format	H.265 / H.264 / MJPEG
Frame Rate	Up to 30 FPS
Triple Streaming	2 for PC live view, 1 for mobile live view
Bitrate Adjust	CBR / VBR
Video Adjustment	Brightness, Contrast, Hue, Saturation, Sharpness, Gain control, WDR, Noise Reduction, Day/Night color mode, Mirror, Noise Reduction, Flip
Audio Format	G.711 (64Kbps)G.726 (24Kbps / 32Kbps)
Privacy Mask	3 definable areas
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, IEEE 802.1x port-based authentication, QoS/DSCP
Firmware Upgrade	HTTP mode, can be upgraded remotely

Micro SD Card Management

Recording Trigger	Motion Detection, IP check, Network break down (wire only), Schedule, DI
Video Format	Video (AVI), Snapshot (JPEG)
Playback / Delete	Yes



Network

Ethernet	10 / 100 Base-T
Wireless	802.11b/g/n, supports WEP,WPA-PSK,WPA2-PSK
Network Protocol	IPv6, IPv4, HTTP, HTTPS, SNMP, QoS/DSCP, Access list, IEEE 802.1X, RTSP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour

Remote Client Access

Client Software	Microsoft IE 9 or above Safari V5.1 or above
Connected Clients	Android => "wecam_p2p" iOS=> " wecam_p2p "
PC Requirement	Up to 10 clients simultaneously OS: Windows 7, Vista, XP Suggested Hardware: Intel Core 2 Duo 2.53GHz, RAM: 1GB Graphic card: 128MB onboard