



4MP_4.2X_P-IRIS Network Camera

CAM6095QIR-PoE

CAM6095QIR-W



Specification

- ▶ 4Mega-Pixel CMOS Sensor
- ▶ Smart Stream , P-IRIS
- ▶ 4.2X Bulid-in Zoom Lens,Smart Focus System for Remote Focus Adjustment
- ▶ H.265 /H.264/MJPEG Compression
- ▶ IR-Cut Filter Mechanism ,IR LED 30M
- ▶ ROI Function , IP66
- ▶ Two-way audio, Digital In/Out
- ▶ Free 36CH recording software & App (wecam_p2p)

Hardware		System	
CPU	Multimedia SoC	Video Resolution	2592x1520@25fps, 1920x1080, 1280x720, 640x480@30fps
RAM	512MB	Video Format	H.265 / H.264 / MJPEG
Flash ROM	32MB	Frame Rate	Up to 30 FPS
Image Sensor	1/3" Mega-Pixel CMOS Sensor	Triple Streaming	2 for PC live view, 1 for mobile live view
Lens	2.8-12mm 4.2X Bulid-in Zoom , P-IRIS @F1.4	Bitrate Adjust	CBR / VBR
Sensitivity	Color: 0.08 lux (AGC ON) B/W: 0.03 lux (AGC ON)	ROI	Region Of Interest
ICR	IR Cut Filter Mechanism	Video Adjustment	Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Night Mode, WDR, Flip, Mirror, Noise Reduction, Day/Night Adjustable
IR LEDs	28Units 5φ +2 Units High Power	Audio Format	G.711 (64Kbps)G.726 (24Kbps / 32Kbps)
IR Distance	30M	Privacy Mask	3 definable areas
Audio Input	1 Microphone in (3.5mm phone jack)	Security	Password protection, IP address filtering, HTTPS encrypted data transmission, IEEE 802.1x port-based authentication for network protection, QoS/DSCP
Audio Output	1 Line out (3.5mm phone jack)	Firmware Upgrade	HTTP mode, can be upgraded remotely
Digital In / Out	1 Digital in / 1 Digital out	Event System	
Power Supply	CAM6095QIR-W: Power Adaptor: DC 12V, 1.5A CAM6095QIR -PoE (built-in PoE Splitter): PoE: PoE (IEEE 802.3af) Or, Power Adaptor: DC 12V, 1.5A	Event Trigger	Motion Detection, Digital In, Tampering Detection, Sound Detection(MIC-in)
Dimensions	77.4mm(Φ) x H125.5mm	Trigger Actions	Send Email, Send to FTP, Save to SD Card, Save to Samba HDD, Digital Out
Operating Temp.	-20°C ~ +60°C	Motion Area	12 definable areas
Weight	720g	Pre / Post Alarm	Yes, configurable time
Network		Remote Client Access	
Ethernet	10 / 100 Base-T	Client Software	Microsoft IE 11 or above Safari V5.1 or above Android => "wecam_p2p" iOS=> "wecam_p2p"
Wireless	CAM6095QIR-W: 802.11b/g/n, supports WPA-PSK, WPA2-PSK, WEP	Connected Clients	Up to 10 clients simultaneously
Network Protocol	IPv4/IPv6, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, Samba, Bonjour	PC Requirement	OS: Windows 7, Vista, OR above Suggested Hardware: Intel Core 2 Duo 2.8GHz, RAM: 4GB Graphic card: 128MB onboard
Micro SD Card Management(Optional)			
Recording Trigger	Motion Detection, DI, IP Check, Network break down(wire only) ,Schedule		
Video Format	Video (AVI), Snapshot (JPEG)		
Playback / Delete	Yes		