

H.264 Mega-Pixel CMOS IP Camera

CAM641



- ▶ 1.3 Mega-Pixel CMOS Sensor
- ▶ H.264/ MJPEG/ MPEG4 Triple mode & streaming
- ▶ 15FPS@1280x1024, 30FPS@640x480
- Onvif Compliant
- 2-way audio
- Free App (wecam_p2p) for monitoring via smart phone
- ▶ Free 36CH recording software

Specification

Hardware

CPU ARM 9, 32 bit RISC

RAM 256MB Flash 16MB

Image Sensor 1/4" CMOS, 1.3 Mega pixels Lens Fixed Lens 6 mm, F1.6

Lens Changeable Yes, CS mount

Illumination 1.5 lux

Audio In Built-in microphone
Audio Out 3.5 mm headphone jack

Power Supply DC 12V, 1A

Dimensions W55 x H50 x D143 mm

Temperature $-10^{\circ}\text{C} \sim +45^{\circ}\text{C}$

Network

Ethernet 10/ 100 Base-T

Network Protocol HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP,

SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

Event System

Event Trigger Motion Detection

Trigger Actions Send Email, Send to FTP

Client Requirements

OS Windows XP / Vista / Win 7

Browser IE7,IE8, FireFox, Safari, Chrome, Opera
Suggested Intel Core 2 Duo 1.66G, RAM:1024MB
Graphic card: 128MB onboard RAM

Compression Format

System

Video Resolution 1280x1024, 1280x960, 1280x720,

800x600, 640x480, 320x240,160x120 H.264 / MJPEG/ MPEG4(for 3GPP)

Frame Rate Up to 15FPS@1280x1024

Up to 30 FPS@640x480

Video Bitrate Adjust CBR, VBR

Dual Streaming Yes

3GPP Yes, Live view with 3G mobile phone

Image Snapshot Yes

Video Adjust Brightness, Contrast, Exposure,

Saturation, Sharpness, AGC, Frame

Rate at Night, Indoor/Outdoor

Motion Detection Yes, 3 different areas
Pre/ Post Alarm Yes, configurable
Privacy Mask Yes, 3 different areas
Security Password protection

Connection Up to 10 clients simultaneously

Firmware Upgrade HTTP mode, remotely

Audio Yes, 2-way

Package List



