



IR-15M_4MP_Network Vandal Camera

CAM6593QIR(PoE)



- ▶ 4Mega-Pixel CMOS Sensor
- ▶ Resolution up to 2688x1520 @30FPS
- ▶ H.264/MJPEG formats & triple stream
- ▶ Embedded ICR and 15-meters IR LED for day & night 24-hours surveillance
- ▶ IP66 & Vandal proof standard
- ▶ Free 36CH recording software
- ▶ Free App (wecam_p2p) for monitoring via Android/iOS smart phone

Specification

Hardware

CPU	Multimedia SoC
RAM	512MB
Flash ROM	32MB
Image Sensor	1/3" Mega-Pixel CMOS
Lens	3.6mm F2.1, Mega-Pixel lens
IR Distance	15 Meters
IR LED	15 LEDs, 850nm
Min. Illumination	Color: 0.15 lux (AGC ON) Mono: 0.08 lux (AGC ON)
Day / Night	Built-in Mechanism IR Cut Filter (ICR)
DC IRIS	Yes
Shutter Time	Auto: Indoor, Outdoor Manual: 1/30 ~ 1/1000 sec
Housing	IP66 water proof / IK10 vandal proof
Power Supply	DC 12V Max: 4.08W(IR ON); 2.88W(IR OFF) PoE Max: 5.28W(IR ON); 4.32W(IR OFF)
Consumption	Max. 5.28Watt
Dimensions	Φ105x H82.2 mm
Operating Temp.	-20°C ~ +60°C

System

Video Resolution	2688x1520@30fps, 1920x1080@30fps, 1280x720@30fps, 640x360@30fps
Video Format	H.264 / MJPEG
Frame Rate	Up to 30 FPS
Triple Streaming	2 for PC live view, 1 for mobile live view
Bitrate Adjust	CBR / VBR, up to 10Mbps
Video Adjustment	Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Night Mode, WDR, Flip, Mirror, Noise Reduction, Day&Night Adjustable
Privacy Mask	3 definable areas
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1x port-based authentication, QoS/DSCP
Firmware Upgrade	HTTP mode, can be upgraded remotely

Event System

Event Trigger	Motion Detection, Tampering Detection
Trigger Actions	Send Email, Send to FTP, Save to SD Card, Save to Samba HDD
Motion Area	3x4 definable areas

Network

Ethernet	10 / 100 Base-T
Network Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, RTP/RTSP, UDP, 3GPP, SMTP, FTP, Samba, PPPoE, DHCP, Access list, DDNS, NTP, UPnP, SNMP, QoS/DSCP, IP Filter, IEEE 802.1x, Bonjour, RTSP, SMTP
Onvif Compliance	Onvif V2.4.2, 1.01

Micro SD Card Management

Recording Trigger	Motion Detection, Digital In, Tampering Detection, IP Check, Network Disconnect
Schedule	Snapshot with schedule
Video Format	Video (AVI), Snapshot (JPEG)
Playback / Delete	Yes

Remote Client Access

Client Software	Microsoft IE 9 or above Safari V5.1 or above
	Android => "wecam_p2p" iOS => "wecam_p2p"
Connected Clients	Up to 10 clients simultaneously
PC Requirement	OS: Windows 7, Vista, XP Suggested Hardware: Intel Core 2 Duo 2.53GHz, RAM: 1GB Graphic card: 128MB onboard

