



# 16 CH\_mini\_P2P Network Video Recorder

## NVR6216MP



- ▶ Easy P2P connection via UID ( QR code )
  - ▶ Linux-based standalone NVR, H.264 decoding
  - ▶ Manage up to 16 IP cameras, Supports 5 Mega-pixel
  - ▶ Plug & Play, Real-time Display & Audio Backup & Playback for all channels
  - ▶ Support rapid "Smart-Search" for specific recording time-duration & seeking for some occurrences more easily.
  - ▶ Support time-point backup function under Ethernet remote control mode
  - ▶ USB3.0 connector connects to external storage
  - ▶ Support HDD up to 8TB Max
  - ▶ Remote client access and management
- Free App (wecam\_p2p, iCAM Smart )for monitoring

### Specification

#### System

CPU / OS	Multimedia SoC / Embedded Linux
Network	Gigabit Ethernet port x1
Video Output	VGA x 1, HDMI x 1, up to 1920x1080
USB Connector	USB 2.0 x 1, USB 3.0 x 1 ( for mouse or USB storage)
Audio Input	3.5mm jack to connect microphone
Audio Output	3.5mm jack to connect amplified speaker
Record Storage	Internal Storage: SATA HDD x 1,( up to 8TB total) External Storage: USB Backup Disk
Network Protocol	HTTP, TCP/IP, RTP/RTSP, SMTP, FTP, PPPoE, DHCP (Server & Client), DDNS, NTP, UPnP
P2P Link Intention	Scan QR-code into APP , ( or connect camera in LAN first.)
Mouse Control	Yes
Authority Control	Password protection
Setting guide	Setup Wizard
System Monitor	Watchdog
Power Supply	DC 12V, 3A (without HDD)
Dimensions	W60 x H161 x D208 mm
Operating Temp.	0~45°C / 32~113°F
Humidity	0~80% RH (non-condensing)

#### Live View

Split Screen	1, 4,9,10,13,16,Full screen, ch-shifting
Event Notification	Pop-up information/ buzzer /email notification
PTZ Control	Yes ,(CAM6_series preferred)
Digital Zoom	Yes
Privacy Mask	Yes
Channel Identify	Yes, Max. 256 characters for channel name

#### Playback and Backup

Search Method	Smart-Search(IVS), Date / Time , Event ; (select from calendar)
Backup	USB / FTP /SMABA storage; (Auto or Manual by Scheduled time)

#### Event System

Alarm Event	Motion detection / Digital Input / video loss / network disconnection / HDD error
Trigger Actions	Recording / E-Mail / Buzzer Warning

#### Recording

Record Format	H.264 video stream
Record Resolution	Depends on IP camera Up to 5 Mega-pixel 2592x1944
Record FPS	Depends on IP camera, up to 30FPS
Record Mode	Manual / Schedule / Event
Pre /Post Recording	5~60 sec
HDD Management	Overwrite when HDD is full

**Video / Audio**

Channel	Max. 16 channels recording and display
Support IPCam	Up to 5 Mega-pixel 2592x1944 H.264 compression mode
Frame Rate	Up to 30FPS per channel
Throughput	Up to 72Mbps
2-Way Audio	Hearing voice from IP camera Chatting or broadcasting to IP cameras

**Remote Client Access**

Client Software	Microsoft IE 10 or above Safari V5.1 or above Android => "wecam_p2p" iOS=> "iCAM Smart"
Connected Clients	Up to 4 clients simultaneously
Remote Operation	Live view / Playback / Setup / Backup
PC Requirement	OS: Windows 7, 10 Suggested Hardware: Intel Core 2 Duo 2.53GHz, RAM: 1GB

**Connection Diagram**

Remote-site  
Live-View, monitoring

