



16CH Linux Network Video Recorder

NVR6516L(P)



- ▶ Support up to 16 channel H.265/H.264 IP camera
- ▶ Manage up to 16 channel PoE for IP cameras input
- ▶ Supports up to 8 Mega-pixel
- ▶ Power management for PoE channel
- ▶ Plug & play for easy installation
- ▶ Support e-SATA external storage
- ▶ Support RAID1/5 (optional)
- ▶ VGA& HDMI dual output, HDMI up to 4K2K
- ▶ Playback Smart search
- ▶ E-MAP
- ▶ Manual / schedule / event recording
- ▶ Free App (wecam_p2p) for monitoring via Android / iOS smart phone
- ▶ Peer to Peer (NVR65 Series LP)

Specification

System

Video Output	VGA x 1 up to 1080P HDMI x 1, up to 4K2K
USB Connector	USB 2.0 x 3
Audio Input	3.5mm jack to connect microphone
Audio Output	3.5mm jack to connect amplified speaker
Record Storage	Internal Storage: SATA HDD x 8 External Storage: Local USB2.0x3, eSATA: x2 RAID: RAID 1/5 (Optional)
Power Supply	AC 100~240V
Power Output	RJ-45 x 16, PoE 802.3at
Max. Power supply	190W
Operating Temp.	0~45°C / 32~113°F
Humidity	0~80% RH (non-condensing)
GPIO	4 Alarm in/ 1 Relay out
WAN Ethernet	RJ-45 x1, 10/100/1000 Mbps
LAN Ethernet	RJ-45 x16, 10/100 Mbps

Recording

Record Mode	Manual / Schedule / Event
Pre Recording	5~60 sec
Playback search	Timeline search, Event list search, Smart search

Remote Client Access

Client Software	Microsoft IE 11 or above Chrome Safari V5.1 or above Android => "wecam_p2p" iOS=> "wecam_p2p"
Connected Clients	Up to 10 clients simultaneously

Video / Audio

Channel	Max.25 channels recording and display
IPCam Video input	36 channels
Split screen display	16CH(1, 4, 9, 16)
Decompression	H.265, H.264
IP Cam Resolution	Up to 4K2K
Throughput	100Mbps