



Z-wave Flood + Humidity + Temperature sensor **WSS111**

Features

- ▶ Z-Wave 500 series module inside
- ▶ Higher output power to enhance the communication range (+5dBm output power as compared to -2.5dBm 300 series)
- ▶ Integrate Flood Sensor, Humidity Sensor and Temperature Sensor
- ▶ High sensitive linear flood detector
- ▶ 1700mAh CR123A Lithium battery to guarantee 7 years battery life
- ▶ Extremely low power consumption
- ▶ Low power indication
- ▶ Slim, small and elegance
- ▶ Easy installation
- ▶ EN 301 489-1, EN 301 489-3 EN 300 220-1, EN 300 220-2
- ▶ EN62479, EN60950 FCC Part 15 B, FCC Part 15 C

Specification

Hardware

Operating Voltage	3.0 V by CR123A
Low Battery Voltage	2.6 V
Standby Current	5.0uA
Battery	CR123A_1700 mA
Battery Life	7 years
RF Range	Z-wave Min. 40M indoor; Min. 100M outdoor

Mechanical

Dimension	96(L) x 28(W) x 23(H) mm
Weight	39.6 g (Net Weight)

Environment

Operating Temp.	-10 ~ 40° C
Humidity	85% RH max