



Outdoor 12X PTZ IP Dome Camera

CAM420B / CAM420B-PoE



- ▶ Remote Pan-Tilt-Zoom control
- ▶ MPEG4 / MJPEG Dual mode & Dual streaming
- ▶ Optical Zoom: 12X
- ▶ Support SD card for event recording
- ▶ 2-way audio
- ▶ Digital I/O: 1 in/ 1 out
- ▶ 3GPP for monitoring via 3G mobile phone
- ▶ Embedded PoE (CAM420B-PoE)
- ▶ Free 36CH recording software

Specification

Hardware

CPU/ RAM/ ROM	ARM 9, 32 bit RISC/ 64MB/ 8MB
Image Sensor	1/4" CCD
Lens	Auto focus zoom lens 3.8 ~ 45.6 mm, F1.6,
Illumination	0.1 lux
Day/ Night	Auto, IR Cut Filter
Video Out	1 Analog video out (RCA connector)
Audio In	Built-in microphone or 3.5 mm headphone jack
Audio Out	3.5 mm headphone jack
Digital I/O	1 In / 1 Out
Water Proof	IP-66 standard
Power Supply	CAM420B: DC 12V, 1A CAM420B-PoE: Use PoE: PoE Injector (IEEE 802.3af) Or, use Power Adaptor: DC 12V, 1A
Dimensions	Φ221 x H489 mm

Network

Ethernet	10/ 100 Base-T
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

SD Card Management

Recording Trigger	Motion Detection, Sensor In, IP Check, Network Disconnect
Video Format	Video (AVI), Snapshot (JPEG)
Video Playback	Yes

Package List

Camera, Power Adapter (not included with PoE model), Housing, Pendant-mount Stand, Screw&Tool, CD-ROM, Quick Guide

*Optional Indoor Model - CAM420

System

Video Resolution	NTSC: 720x480, 704x480, 352x240, 176x120 PAL: 720x576, 704x576, 352x288, 176x144
Compression Format	MPEG-4 / MJPEG
Frame Rate	Up to 30 FPS
Video Bitrate Adjust	CBR, VBR
Dual Streaming	Yes
3GPP	Yes, Live view with 3G mobile phone
Pan/ Tilt/ Zoom Control	Yes, remotely
Zoom Ratio	Optical: 12X, Digital: 4X
Pan/ Tilt Angle	Pan: 270°, Tilt: 120°
Preset Point	9 Preset points
Patrol	Yes, one-time per click
Auto Pan	Yes, one-time per click
Pan/ Tilt Speed Control	Yes
Motion Detection	Yes, 3 different areas
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way

Event System

Event Trigger	Motion Detection, Sensor In
Trigger Actions	Send Email, Send to FTP, Save to SD Card, Digital Out

Client Requirements

OS	Windows XP / Vista / Win 7
Browser	IE7,8 / FireFox / Chrome / Opera / Safari
Suggested	Intel-C 2.0G, RAM: 512MB, Graphic card: 64MB onboard RAM