Network Surveillance Solutions

IR-80M Mega-Pixel Progressive CCD IP Camera

<u>CAM432 /</u> CAM432-PoE

- Mega-Pixel Sony progressive CCD
- MPEG4 / MJPEG Dual mode & Dual streaming
- Day & night functionality for 24-hour surveillance
- ▶ IR distance up to 80 meters
- 2-way audio
- Digital I/O: 2 in / 2 out
- ▶ 3GPP for monitoring via 3G mobile phone
- Embedded PoE (CAM432-PoE)

Specification

Hardware

CPU	ARM 9, 32 bit RISC
RAM	64MB
Flash	16MB
Image Sensor	1/3" Sony Progressive CCD, 520 TV lines
Lens	Vari-focal 10 ~ 40 mm, F1.4 ~ 360
Illumination	IR On: 0 lux
Infrared LED	850nm / 8 LED
IR Distance	80 Meters
Lens Changeable	Yes, CS Mount
Support DC IRIS	Yes
Video Out	1 Analog video out with BNC connector (for
	lens adjustment only)
Audio In	Built-in microphone
Audio Out	1 Line out (RCA connector)
Digital I/O	2 In / 2 Out
Water Proof	IP-66 standard
Power Supply	CAM432: DC12V, 2A
	CAM432-PoE:
	 Use PoE Injector (IEEE 802.3at)
	 High power PoE Injector is included
Dimensions	W170 x H280 x L470 mm
Network	
Ethernet	10/ 100 Base-T
Network Protocol	HTTP TCP/IP RTP/RTSP 3GPP NTP SMTP

Network Protocol HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

Package List

Camera, Power Adapter (not included with PoE model), Stand, Screws&Tool, CD-ROM, Quick Installation Guide

http://www.a-soni.com

Asoni

	Free 36CH recording software		
	System		
	Video Resolution	MJPEG: 1280x960, 640x480,	
		MPEG-4: 640x480, 320x240,	
		176x144	
es	Compression Format	MPEG-4 / MJPEG	
	Frame Rate	MJPEG: Up to 15 FPS@1280x960	
		MPEG-4: Up to 30 FPS@640x480	
	Dual Streaming	Streaming 1: MJPEG	
		Streaming 2: MPEG-4	
	3GPP	Yes, Live view with 3G mobile phone	
	Image Snapshot	Yes	
(for	Video Adjust	Brightness, Contrast, Saturation, Hue,	
		Sharpness, AES, BLC, AGC, Day/Night	
	Motion Detection	Yes, 3 different areas	
	Pre/ Post Alarm	Yes, configurable	
	Security	Password protection	

C, AGC, Day/Night Password protection Up to 10 clients simultaneously Firmware Upgrade HTTP mode, remotely Yes, 2-way

Event System

Connection

Audio

Event Trigger	Motion Detection, Sensor In
Trigger Actions	Send Email, Send to FTP, Digital Out

Client Requirements

OS	Windows XP / Vista / Win 7
Browser	IE7,IE8, FireFox, Safari, Chrome, Opera
Suggested	Intel-C 2.0G, RAM: 512MB,
	Graphic card: 64MB onboard RAM