



CMOS IP Camera

CAM438 / CAM438W

- ▶ MPEG4 / MJPEG Dual codec compression
- ▶ MPEG4 / MJPEG Dual streaming
- ▶ 30FPS@640x480
- ▶ 2-way audio
- ▶ 3GPP for monitoring via 3G mobile phone
- ▶ Embedded Wireless (CAM438W)
- ▶ Free 36CH recording software

Specification**Hardware**

CPU	ARM 9, 32 bit RISC
RAM	32MB
Flash	8MB
Image Sensor	1/4" CMOS
Lens	Board Lens 4 mm, F2.0
Illumination	1 lux
Audio In	Built-in microphone
Audio Out	3.5 mm headphone jack
Power Supply	DC 12V, 1A
Dimensions	W59 x H93.7 x D45.5 mm

Network

Ethernet	10/ 100 Base-T
Wireless	802.11b/g (CAM438W)
	WPA-PSK, WPA2-PSK, WEP 64/ 128 bit
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

Client Requirements

OS	Windows XP / Vista / Win 7
Browser	IE7, IE8, FireFox, Safari, Chrome, Opera
Suggested	Intel-C 2.0G, RAM: 512MB, Graphic card: 64MB onboard RAM

System

Video Resolution	640x480, 320x240, 160x120
Compression Format	MPEG-4 / MJPEG
Frame Rate	Up to 30 FPS
Video Bitrate Adjust	CBR, VBR
Dual Streaming	Yes
3GPP	Yes, Live view with 3G mobile phone
Image Snapshot	Yes
Video Adjust	Brightness, Contrast, Saturation, Sharpness, Exposure, AGC, BLC, Night Mode
Motion Detection	Yes, 3 different areas
Pre/ Post Alarm	Yes, configurable
Security	Password protection
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way

Event System

Event Trigger	Motion Detection
Trigger Actions	Send Email, Send to FTP

Package List

CAM438 Camera, Power Adapter, Ethernet Cable, Stand, Screws, Antenna (CAM438W), CD-ROM, Quick Installation Guide