Network Surveillance Solutions



2 Mega-Pixel CMOS Day&Night IP Camera

CAM613M(W, PoE)

- 2 Mega-Pixel CMOS sensor
- ▶ H.264/ MJPEG/ MPEG4 Triple mode & streaming
- Onvif Compliant
- Support SD card for event recording
- Support DC IRIS

System

- 2-way audio / 1 Analog video output
- Digital I/O: 1 in/ 1 Relay out
- ▶ 3GPP for monitoring via 3G mobile phone
- Embedded Wireless (CAM613MW)
- Embedded PoE (CAM613M-PoE)

Specification

Hardware

CPU/ RAM/ Flash	ARM 9, 32 bit RISC/ 256MB/ 16MB
Image Sensor	1/3" CMOS, 2 Mega-Pixels
Lens	Fixed Lens 3.7 mm, Mega Pixel @ F1.8
Illumination	0.5 lux
Day/ Night	Optional Mechanism IR Cut Filter (ICR)
Lens Changeable	Yes, CS Mount
Support DC IRIS	Yes
Video Out	1 Analog video out (BNC connector)
Audio In	Built-in microphone
Audio Out	1 Line out
Digital I/O	1 In / 1 Relay out
Power Supply	CAM613M/ CAM613MW: DC 12V, 1A
	CAM613M-PoE:
	Use PoE: PoE Injector (IEEE 802.3af)
	Or, use Power Adapter: DC 12V, 1A
Dimensions	W58 x H65 x D131.5 mm
Temperature	-10℃ ~ +45℃

/ISON

Network

Ethernet	10/ 100 Base-T
Wireless	802.11b/g (CAM613W)
	WEP,WPA-PSK,WPA2-PSK
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, UDP
	FTP, SMTP, PPPoE, DHCP, DDNS, UPnP

SD Card Management

Recording Trigger	Motion Detection, Sensor In, IP Check,
	Network Disconnect
Video Format	Video (AVI), Snapshot (JPEG)
Schedule	Snapshot during schedule
Video Playback / Delete	Yes

http://www.a-soni.com

E-mail: marketing@a-soni.com

Video Resolution 1600x1200,1280x1024,1280x960,1280x720, 800x592,640x480, 320x240, 176x144 **Compression Format** H.264 / MJPEG / MPEG-4 (3GPP only) Frame Rate Up to 15 FPS@1600x1200 Up to 30 FPS@1280x720 Video Bitrate Adjust CBR, VBR **Triple Streaming** Yes (2 for live view, 1 for 3GPP) 3GPP Yes, Live view with 3G mobile phone Video Adjust Night Mode, Brightness, Contrast, BLC, Sharpness Motion Detection Yes, 3 different areas Pre/ Post Alarm Yes, configurable Security Password protection Connection Up to 10 clients simultaneously Firmware Upgrade HTTP mode, remotely Audio Yes, 2-way **Event System**

Event Trigger **Trigger Actions** Motion Detection, Sensor In Send Email, Send to FTP, Save to SD Card, Relay Out

Client Requirements

OS	Windows XP / Vista / Win 7
Browser	IE7,IE8, FireFox, Safari, Chi
Suggested	Intel Core 2 Duo 1.66GHz, F
	Graphic card: 128MB onboa

Fox, Safari, Chrome, Opera Duo 1.66GHz, RAM: 1GB d: 128MB onboard RAM

Package List



Antenna: CAM613MW

PoE Model doesn't include ower adaptor