



Outdoor 12X H.264 PTZ Dome IP Camera

**CAM620B/CAM620B-PoE**



- ▶ Remote Pan-Tilt-Zoom control
- ▶ H.264/ MPEG4/ MJPEG Triple mode & streaming
- ▶ Optical Zoom: 12X
- ▶ Onvif Compliant
- ▶ Support SD card for event recording
- ▶ 2-way audio
- ▶ Digital I/O: 1 in/ 1 out
- ▶ 3GPP for monitoring via smart phone
- ▶ Embedded PoE (CAM620B-PoE)
- ▶ Free 36CH recording software

**Specification**

**Hardware**

CPU/ RAM/ Flash	ARM 9, 32 bit RISC/ 256MB/ 16MB
Image Sensor	1/4" CCD
Lens	Auto focus zoom lens, 3.8 ~ 45.6 mm, F1.6
Illumination	0.1 lux
Day/ Night	Auto, IR Cut Filter
Video Out	1 Analog video out (RCA connector)
Audio In	Built-in microphone or 3.5 mm headphone jack
Audio Out	3.5 mm headphone jack
Digital I/O	1 In / 1 Out
Water Proof	IP-66 standard
Power Supply	CAM620B: DC 12V, 1A CAM460B-PoE: Use PoE: PoE Injector (IEEE 802.3af) Or, use Power Adaptor: DC 12V, 1A
Dimensions	Φ221 x H489 mm
Temperature	-10°C ~ +45°C (heater is optional)

**Network**

Ethernet	10/ 100 Base-T
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

**SD Card Management**

Recording Trigger	Motion Detection, Sensor In, IP Check, Network Disconnect
Video Format	Video (AVI), Snapshot (JPEG)
Schedule	Snapshot during schedule
Video Playback	Yes

**Event System**

Event Trigger	Motion Detection, Sensor In
Trigger Actions	Send Email, Send to FTP, Save to SD Card, Digital Out

**\*Optional Indoor Model - CAM620**

**System**

Video Resolution	NTSC: 720x480, 704x480, 352x240, 176x120 PAL: 720x576, 704x576, 352x288, 176x144
Compression Format	H.264 / MJPEG / MPEG-4 (3GPP only)
Frame Rate	Up to 30 FPS
Video Bitrate Adjust	CBR, VBR
Triple Streaming	Yes ( 2 for live view , 1 for 3GPP)
3GPP	Yes, Live view with 3G mobile phone
Pan/ Tilt/ Zoom Control	Yes, remotely
Zoom Ratio	Optical: 12X, Digital: 4X
Pan/ Tilt Angle	Pan: 270°, Tilt: 120°
Preset Point	9 Preset points
Patrol	Yes, one-time per click
Auto Pan	Yes, one-time per click
Pan/ Tilt Speed Control	Yes
Motion Detection	Yes, 3 different areas
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way

**Client Requirements**

OS	Windows XP / Vista / Win 7
Browser	IE7, IE8, FireFox, Safari, Chrome, Opera
Suggested	Intel-C Dual Core 1.66G, RAM: 1024MB, Graphic card: 128MB onboard RAM

**Package List**



PoE Model doesn't include power adaptor