



Analog Vandal Dome Camera

ATC 11 / ATC11-IR series



Specifications

ATC-11 Series

Pick-Up Device:	1/3" CCD Image Sensor
Picture Elements(H*V):	NTSC: 512*492, PAL: 500*582 NTSC: 768*492, PAL: 752*582
H. Sync. Frequency:	NTSC:15.734 KHz, PAL:15.625 KHz
V. Sync. Frequency:	NTSC:59.94 Hz, PAL:50 Hz
Horizontal Resolution:	420 TV lines
Synchronization:	Internal/DC type; Line Lock/AC type Only
Sensitivity:	0 Lux when IR LED On
Scanning System	2:1 InterLance
Electronic Shutter:	ON/ OFF Switchable, Auto Range 1/50(1/60) up to 1/100,000 sec
Gain Control:	AUTO
Lens	3.7-12mm Auto IRIS Vari-Focal Day & Night Lens
Gamma Correction	0.45
S/N Ratio	More than 48 dB(AGC off)
Video Output	1 Vp-p, 75 Ohms
Power Supply	DC 12V or AC 24V
Power Consumption	270/300 mA
Weather Proof IP Rating	IP66
Storage Temperature	-30°C ~ +60°C
Operating Temperature	-10°C ~ +45°C
Dimensions(H*W)	φ137x 93.7 mm
Weight	740 g

ATC-11-IR Series

Pick-Up Device:	1/3" CCD Image Sensor
Picture Elements(H*V):	NTSC: 512*492, PAL: 500*582 NTSC: 768*492, PAL: 752*582
H. Sync. Frequency:	NTSC:15.734 KHz, PAL:15.625 KHz
V. Sync. Frequency:	NTSC:59.94 Hz, PAL:50 Hz
Horizontal Resolution:	420 TV lines
Synchronization:	Internal/DC type; Line Lock/AC type Only
Sensitivity:	0 Lux when IR LED On
Scanning System	2:1 InterLance
IR ON	<3 Lux
IR Distance	12M
Electronic Shutter:	ON/ OFF Switchable, Auto Range 1/50(1/60) up to 1/100,000 sec
Gain Control:	AUTO
Lens	3.7-12mm Auto IRIS Vari-Focal Day & Night Lens
Gamma Correction	0.45
S/N Ratio	More than 48 dB(AGC off)
Video Output	1 Vp-p, 75 Ohms
Weather Proof IP Rating	IP66
Power Supply	DC 12V or AC 24V
Power Consumption	270/300 mA
Storage Temperature	-30°C ~ +60°C
Operating Temperature	-10°C ~ +45°C
Dimensions(H*W)	φ137x 93.7 mm
Weight	740 g