



P/T Network Dome Camera

CAM412 / CAM412W

- ▶ Remote Pan-Tilt control
- ▶ MPEG4 / MJPEG Dual mode & Dual streaming
- ▶ Support SD card for local record
- ▶ 2-way audio
- ▶ Digital I/O: 1 in/ 1 out
- ▶ 3GPP for monitoring via 3G mobile phone
- ▶ Optional Wireless (CAM412W)
- ▶ Free 36CH recording software

Specification**Hardware**

CPU	ARM 9, 32 bit RISC
RAM	64MB
ROM	8MB
Image Sensor	1/4" Sony CCD
Lens	Board Lens, Focal length 3.6 mm, F2.0
Sensitivity	0.5 lux
Video Out	1 Analog video out (RCA connector)
Audio In	Built-in microphone or 3.5 mm headphone jack
Audio Out	3.5 mm headphone jack
Digital I/O	1 In / 1 Out
Power Supply	DC 5V, 2A
Dimensions	W105 x H128.6 x D105 mm

Network

Ethernet	10/ 100 Base-T
Wireless	802.11b/g (CAM412W) WPA-PSK, WEP 64/ 128 bit
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

SD Card Management

Recording Trigger	Motion Detection, Sensor In, IP Check, Network Disconnect
Video Format	AVI, JPEG
Video Playback	Yes
Delete Files	Yes

Package List

CAM412 Camera, Power Adapter, Ethernet Cable, Mounting Base, Screws, Antenna (CAM412W), CD-ROM, Quick Installation Guide

System

Video Resolution	NTSC: 720x480, 704x480, 352x240, 176x120 PAL: 720x576, 704x576, 352x288, 176x144
Compression Format	MPEG-4 / MJPEG
Frame Rate	Up to 30 FPS
Video Bitrate Adjust	CBR, VBR
Dual Streaming	Yes
3GPP	Yes, Live view with 3G mobile phone
Pan/ Tilt Control	Yes, remotely
Pan/ Tilt Angle	Pan: 270°, Tilt: 120°
Preset Point	9 Preset points
Patrol	Yes, one-time per click
Auto Pan	Yes, one-time per click
Pan/ Tilt Speed Control	Yes
Motion Detection	Yes, 3 different areas
Security	Password protection
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way

Event System

Event Trigger	Motion Detection, Sensor In
Trigger Actions	Send Email, Send to FTP, Save to SD Card, Digital Out

Client Requirements

OS	Windows 2000, XP, 2003, IE6.0
Suggested	Intel-C 2.0G, RAM: 512MB, Graphic card: 64MB