



## Outdoor 30X Network Speed Dome

**CAM430B / CAM430B-PoE**

- ▶ Remote Pan-Tilt-Zoom control
- ▶ MPEG4 / MJPEG Dual mode & Dual streaming
- ▶ Optical Zoom: 30X
- ▶ 32 Preset points, patrol, auto pan
- ▶ 2-way audio
- ▶ Digital I/O: 2 in/ 2 out
- ▶ IP66 water proof standard
- ▶ Optional embedded PoE (CAM430B-PoE)
- ▶ Free 36CH recording software

**Specification****Hardware**

CPU	ARM 9, 32 bit RISC
RAM	64MB
ROM	8MB
Image Sensor	1/4" Sony ExView CCD, 540 TV lines
Lens	30X Zoom Lens 3.3 ~ 99 mm, F1.6 ~ 3.2
Day/ Night	Auto, IR Cut Filter
Sensitivity	Color mode: 0.4 lux Black/White mode: 0.08 lux
Video Out	1 Analog video out (BNC connector)
Audio	1 Line in / 1 Line out (RCA connectors)
Digital I/O	2 In / 2 Out
Water Proof	IP-66 standard
Power Supply	CAM430B: DC 12V, 3A CAM430B-PoE: <ul style="list-style-type: none"> <li>● Embedded PoE Splitter (IEEE 802.3af)</li> <li>● High power PoE Injector is included</li> </ul>
Dimensions	Φ221 x H490 mm

**Network**

Ethernet	10/ 100 Base-T
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

**Client Requirements**

OS	Windows 2000, XP, 2003, IE6.0
Suggested	Intel-C 2.0G, RAM: 512MB, Graphic card: 64MB

**Package List**

Camera, Power Adapter (not included with PoE model), Housing (including fan&heater), Pendant-mount Stand, CD, Quick Guide

\*Optional Indoor Model - CAM430

**System**

Video Resolution	NTSC: 720x480, 704x480, 352x240, 176x120 PAL: 720x576, 704x576, 352x288, 176x144
Compression Format	MPEG-4 / MJPEG
Frame Rate	Up to 30 FPS
Video Bitrate Adjust	CBR, VBR
Dual Streaming	Yes
3GPP	Yes, Live view with 3G mobile phone
Pan/ Tilt/ Zoom Control	Yes, remotely
Zoom Ratio	Optical: 30X, Digital: 4X
Pan Angle	360°, continuous
Tilt Angle	180°
Pan/ Tilt Speed	Variable speed, up to 300°/sec
Preset Point	32 Preset points
Patrol	Patrol for all points, Auto pan
Pan/ Tilt Speed Control	Yes
Focus/ Iris	Auto / Manually
Image Snapshot	Yes
Motion Detection	Yes, 3 different areas
Pre/ Post Alarm	Yes, configurable
Security	Password protection
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way

**Event System**

Event Trigger	Motion Detection, Sensor In
Trigger Actions	Send Email, Send to FTP, Digital Out